



A259

JOB NAME:

FIXTURE TYPE:

2.5" x 9" LINEAR PENDANT LUMINAIRE

FEATURES

- Available in nominal lengths up to 8'-0" sections. Custom lengths are available upon request.
- Sleek rectangular shape fits well into modern architectural schemes. Standard color is white.
- This fixture is well balanced and is easy to install using either stems or adjustable aircraft cable. Wall mounting is also available.
- Light distribution is 95% indirect. We offer various shielding options for the direct lighting component, pattern A12 acrylic lens is standard.
- Fixture may be used in straight runs or in square/angled patterns. All cross T's and corner couplings are made of cast aluminum.

SPECIFICATIONS

- **HOUSING**
Durable strong extruded aluminum housing, end caps are made of die-cast aluminum.
- **ELECTRICAL**
Energy saving, electronic, class P, high power factor ballasts are standard. All ballasts comply with minimum Federal Energy Efficiency standards.
- **FINISH**
All housings are post-painted with a polyester powder coat with smooth finish. Textured finishes are available upon request.
- **SHIELDING**
Pattern A12 acrylic lensing is standard.
- **CERTIFICATION**
All units bear UL Label and Made in USA label.



A259 Luminaire

Ordering Matrix

MODEL	LENGTH	# OF LAMPS	LAMP/BALLAST	SHIELDING		MOUNTING	VOLTAGE	OPTIONS
				DIRECT /	INDIRECT			
A259	48"	1	T8/EB	PB	SO	AC	120	EM
	96"	2	T5/EB	PS	OP	ST	277	DM
	TD	3		PF	AL	CH	UNV	HO
	XX			AL	DC	XX		CC
				SO				

TD: Tandem Run XX: Special Length	T8: Electronic Ballast T5: Electronic Ballast	AC: Aircraft Cable ST: Stem, 24" Standard CH: Chain Mounting XX: Custom Mounting	EM: Emergency Backup HO: High Output Lamps DM: Dimming Ballast CC: Custom Color
--	--	---	--

<u>Direct Configuration</u>	
PB: Parabolic Louver, semi-specular finish	SO: Solid Top, No indirect lighting
PS: Parabolic Specular Louver, specular finish	OP: Open Top
PF: Parabolic Specular Louver, specular finish	AL: Acrylic Lens, ribbed
AL: Acrylic Lens, pattern 12 standard	DC: Dust Cover, clear acrylic
SO: Solid Bottom, no direct light	

Example: If you wanted to specify an A259 fixture with 2 lamps, 8'-0" in length, T8 electronic ballast with a semi-specular parabolic baffle shielding and an open top, to be mounted on aircraft cable, powered by 120 volt with a dimming ballast, the model number would read as follows:

A259 - 96 - 2 - T8/EB - PB/OP - AC - 120 - DIM

