

A67

JOB NAME:

FIXTURE TYPE:



A67 Luminaire (Shown with white cross blade)

FEATURES

- Available in nominal lengths up to 8'-0" sections, T5 or T8 operation, custom lengths available upon request. For continuous runs please consult factory with specific wiring instructions.
- Extruded aluminum housing with options of cross baffle, lens or parabolic louver shielding.
- Simple clean linear lines allow for this fixture to blend aesthetically into almost any space.
- Corner and angled intermediate couplings are available when fitting this fixture into a specific design scheme.
- Mounting can be accomplished using adjustable aircraft cables or rigid stems. Wall mount is also available.

SPECIFICATIONS

- **HOUSING**
Housing constructed of extruded aluminum.
- **ELECTRICAL**
Energy saving and electronic class P, HPF ballasts comply with Federal Energy Efficiency standards.
- **DIFFUSERS**
Pattern A12 acrylic lens is standard. Optional cross blade finish same as fixture housing, unless requested otherwise. When using parabolic aluminum louver, low iridescent finish is standard.
- **FINISH**
All parts finished with polyester powder coat with minimum 89% reflectivity. Standard color is white. Other colors are available upon request.
- **CERTIFICATION**
All units bear UL and Made in U.S.A. labels.



A67 Luminaire

Ordering Matrix

| MODEL | LENGTH | LAMP | MODEL | LENGTH | LAMP |
|---------------|--------|------------|---------------|--------|-------------|
| A67-132T8-4 | 48" | 1-FO32T8 | A67-132T8-8 | 96" | 2-FO32T8 |
| A67-232T8-4 | 48" | 2-FO32T8 | A67-232T8-8 | 96" | 4-FO32T8 |
| A67-332T8-4 | 48" | 3-FO32T8 | A67-332T8-8 | 96" | 6-FO32T8 |
| A67-432T8-4 | 48" | 4-FO32T8 | A67-432T8-8 | 96" | 8-FO32T8 |
| A67-532T8-4 | 48" | 5-FO32T8 | A67-532T8-8 | 96" | 10-FO32T8 |
| A67-128T5-4 | 48" | 1-FO28T5 | A67-128T5-8 | 96" | 2-FO28T5 |
| A67-228T5-4 | 48" | 2-FO28T5 | A67-228T5-8 | 96" | 4-FO28T5 |
| A67-328T5-4 | 48" | 3-FO28T5 | A67-328T5-8 | 96" | 6-FO28T5 |
| A67-428T5-4 | 48" | 4-FO28T5 | A67-428T5-8 | 96" | 8-FO28T5 |
| A67-528T5-4 | 48" | 5-FO28T5 | A67-528T5-8 | 96" | 10-FO28T5 |
| A67-154T5HO-4 | 48" | 1-FO54T5HO | A67-154T5HO-8 | 96" | 2-FO54T5HO |
| A67-254T5HO-4 | 48" | 2-FO54T5HO | A67-254T5HO-8 | 96" | 4-FO54T5HO |
| A67-354T5HO-4 | 48" | 3-FO54T5HO | A67-354T5HO-8 | 96" | 6-FO54T5HO |
| A67-454T5HO-4 | 48" | 4-FO54T5HO | A67-454T5HO-8 | 96" | 8-FO54T5HO |
| A67-554T5HO-4 | 48" | 5-FO54T5HO | A67-554T5HO-8 | 96" | 10-FO54T5HO |

For critical application, verify all dimensions with factory.
For additional Lamp/Ballast options, consult factory.

Options:

- Direct Only – suffix D
- Indirect Only – suffix I
- Direct/Indirect – suffix D/I
- Stem Mount – suffix ST (specify length)
- Aircraft Cable Mount – suffix AC (specify length)
- Wall Mount – suffix WL
- Parabolic Louver – suffix PB
- Cross Blade – suffix BL

