



# RND

JOB NAME

FIXTURE TYPE

**ROUND LUMINAIRE** (shown with white cross baffle and top lens)

## FEATURES

- Available in nominal lengths up to 8'-0" sections, T5 or T8 lamping, 3.5", 4", 6", 7", and 9" diameters.
- Extruded aluminum housing with optional direct shielding of either cross baffled louver or lens.
- Fixture available in straight runs or square patterns. Individual fixtures are standard. For continuous row installations, row lengths must be specified.
- Fixture can be mounted on the wall or with cables or stems. Adjustable wall mount fixtures are also available.
- Direct/Indirect unit is standard. Unit is also available in direct only or indirect only versions.
- Fixture can be easily surface or pendant mounted using cables or stems. Companion wall mounted unit is available.

## SPECIFICATIONS

- **HOUSING**  
Housing constructed of durable extruded aluminum. Die cast aluminum end plates and center couplings provided as required.
- **ELECTRICAL**  
High efficiency electronic ballasts comply with all Federal Energy Efficiency standards.
- **SHIELDING**  
Users have the choice of cross baffles and lenses. Choice of multiple lens and baffle styles available.
- **FINISH**  
All housings post-painted with a smooth white polyester powder coat. Textured finishes and other colors are available upon request.
- **CERTIFICATION**  
All units bear UL and Made in U.S.A. labels. Wet location available upon request (consult factory)



# Round Luminaire

## Ordering Matrix

Model	# of Lamps	Length	Lamp/Ballast	Shielding		Lamping Direct / Indirect		Mounting	Voltage	Options
3.5RND	1	48"	T5/EB	BL	SO	0 or 1	0 or 1	AC	120	EM
4RND	1	96"	T5HO/EB	AL	OP	0 or 1	0 or 1	ST	277	DM
6RND	1, 2, 3 or 4	XX	T8/EB	SO	AL	0, 1 or 2	0, 1 or 2	WM	Dual	CO
7RND	1, 2, 3, 5, or 6					0, 1, 2 or 3	0, 1, 2 or 3			
9RND	1, 2, 3, 5, or 6					0, 1, 2 or 3	0, 1, 2 or 3	WL		

**XX:** Custom Length

**T5:** Electronic Ballast  
**T5HO:** Electronic Ballast  
**T8:** Electronic Ballast

**AC:** Aircraft Cable, 48" Standard  
**ST:** Stem, 24" Standard  
**WM:** Wall Mounted  
**AWM:** Adjustable Wall Mount (4", 6", 9" ONLY)

**EM:** Emergency Backup  
**DM:** Dimming  
**CO:** Color other than white  
**HO:** High Output Lamping  
**WL:** Wet Location (Lens ONLY)

Direct Configuration

**BL:** Cross Blade, white finish  
**AL:** Acrylic Lens, ribbed  
**SO:** Solid Bottom, no direct light

Indirect Configuration

**SO:** Solid Top, no indirect light  
**OP:** Open Top  
**AL:** Acrylic Lens, ribbed

**Example:** If you wanted to specify a 6" RND fixture with 2 lamps, 8'-0" in length, T8 electronic ballast with a white cross baffle and no indirect light and mounted on 24" stems, 120v with emergency back up, the model number would read as follows:

**6RND – 2 – 96 – T8/EB – BL/SO – 2/0 – ST24 – 120 - EM**

