

FHB

JOB NAME:

FIXTURE TYPE:



COMPACT FLUORESCENT HIGH BAY

FEATURES

- Available in 57W or 70W Compact Fluorescent.
- Ideal for factories and warehouses where high levels of illumination are required.
- Pendant mounting (for 3/4" conduit) standard. Optional quick connect hook with 36" cord and NEMA twist plug for chain hanging. (Please provide voltage.)
- Injection molded acrylic refractor is designed to maximize efficiency while controlling glare.
- Acrylic prismatic lenses are standard.

SPECIFICATIONS

- **HOUSING**
Die cast aluminum with thermal chimney. Powder coated white polyester finish.
- **ELECTRICAL**
High Power Factor, constant wattage available in 120, 277, or universal.
- **REFLECTOR**
Hydroformed aluminum is anodized and delivers 80% efficiency.
- **CERTIFICATION**
All units bear UL and Made in U.S.A. labels. Units are UL Listed for damp location.



Compact Fluorescent High Bay

Ordering Matrix

Model	Refractor	Lamps	Wattage	Voltage	Options
FHB	14"	57	18	120	OC
	15"	70	26	277	HL
			32	DUAL	GLR
			42		CP
			57		WG
					FL

- OC:** Occupancy Sensor
- HL:** Hi/Lo Dimming
- GLR:** Fusing
- CP:** Hook, Cord & Plug
- WG:** Wire Guard
- FL:** Flat Lens



DAH: Decorative Aluminum Housing