

AWB

JOB NAME:

FIXTURE TYPE:



COMPACT EXTERIOR WALL PACK

FEATURES

- Die cast aluminum housing with integral hinging feature for ease of maintenance.
- Borosilicate prismatic glass optically designed for optimum light distribution.
- Optional polycarbonate shield for vandalproof protection over the glass refractor.
- Textured anodized aluminum reflector designed in conjunction with diffuser for maximum efficiency.
- Threaded apertures for surface conduit and optional photocell.
- Fully gasketed weather resistant construction.
- For wall mounting directly over standard 4" outlet box or with surface conduit conditions.
- Optional tamperproof hardware.

SPECIFICATIONS

HOUSING

Rugged die cast aluminum housing.

ELECTRICAL

For metal halide lamping, ballast is high power factor, constant wattage auto transformer. Electrical components are mounted to cast aluminum housing for optimum heat dissipation. For high-pressure sodium, ballast is normal power factor reactor type for 120V. High power factor, multi-tap, and most fixed voltages available.

SHIELDING

Borosilicate glass is standard.

FINISH

Baked on premium architectural bronze for maximum durability.

CERTIFICATION

All units bear UL and Made in U.S.A. labels, UL listed for wet locations.



Exterior Wall Bracket

Ordering Matrix

Model	Wattage	Voltage	Finish	Options
AWB	70MH	120	BZ	PC
	100MH	277	BK	WG
	70HPS	480	WH	TP
	100HPS	MULTI	CC	VS
	150HPS			GLR
				QZ
				GS
AWB-F	42CP			EM

MH: Metal Halide
HPS: High Pressure Sodium
CP: Compact Fluorescent

BZ: Bronze Finish
BK: Black Finish
WH: White Finish
CC: Custom Color

PC: Photocell
WG: Wire Guard
TP: Tamperproof hardware
VS: Vandal Shield

GLR: Single Fuse
QZ: Quartz Restrike
GS: Glare Shield (Visor)
EM: 90 Min. Remote Battery Back-Up
 (FOR FLUORESCENTS ONLY)

Example: If you wanted to specify a 42 watt, compact fluorescent AWB fixture with tamperproof hardware and a remote back up with a black finish, the model number would read as follows:

AWB-F – 42 – CP – BK – TP – EM

