

CWPC



JOB NAME:

FIXTURE TYPE:

ENTRANCE/WALKWAY LIGHT

FEATURES

- Ideal for parking areas, entrances, walkways, underpasses, loading docks, recreation areas, and tunnels.
- Heavy-duty die-cast aluminum construction.
- Heat and impact resistant tempered glass lenses.
- Powder coated finish on cast aluminum housing.
- One piece designed anodized aluminum reflector for optimum light efficiency.
- Silicon rubber seal prevents leakage.
- Available as downlight only or up and downlight.
- Lamping up to 175W MH or 150W HPS available.

SPECIFICATIONS

- **HOUSING**
Heavy-duty die cast aluminum housing.
- **ELECTRICAL**
Optimized for 175W MH and 150W HPS. Standard with 120V, 277V, or Multi-tap ballast. High Power Factor and other voltages/lamp options are also available.
- **FINISH**
Powder coated architectural bronze is standard. Other finishes are available upon request.
- **CERTIFICATION**
UL listed for wet locations.



Cut-Off Cast Aluminum Wall Bracket

Ordering Matrix

Model	Wattage	Lamp	Voltage	Finish	Options
CWPC	70	MH	120	BZ	PC
	100	HPS	277	BK	TP
	150		480	WH	GLR
	175		MULTI	CC	QZ
CWPCF	42	CP			EM

MH: Metal Halide
HPS: High Pressure Sodium
CP: Compact Fluorescent

BZ: Bronze Finish
BK: Black Finish
WH: White Finish
CC: Custom Color

PC: Photocell
TP: Tamperproof hardware
GLR: Single Fuse
QZ: Quartz Restrike
EM: 90 Min. Remote Battery Back-Up
 (FOR FLUORESCENTS ONLY)

Example: If you wanted to specify a 150 watt, metal halide CWPCD fixture with tamperproof hardware and black finish, the model number would read as follows:

CWPC – 150– MH – 120 – BK – TP

