



CWPE

JOB NAME:

FIXTURE TYPE:

ENTRANCE/WALKWAY LIGHT

FEATURES

- Ideal for parking areas, entrances, walkways, underpasses, loading docks, recreation areas, and tunnels.
- Heavy-duty die-cast aluminum construction.
- Heat and impact resistant tempered glass lenses.
- Powder coated finish on cast aluminum housing.
- One piece designed anodized aluminum reflector for optimum light efficiency.
- Silicon rubber seal prevents leakage.
- Rotatable wide throw reflector.
- Designed for downlighting or uplighting installations.
- Quick install mounting bracket included.
- Lamping up to 175W MH or 150W HPS and compact fluorescent up to 42W available.

SPECIFICATIONS

- **HOUSING**
Heavy-duty die cast aluminum housing.
- **ELECTRICAL**
Optimized for 175W MH and 150W HPS. Standard with 120V, 277V, or Multi-tap ballast. High Power Factor and other voltages/lamp options are also available.
- **FINISH**
Powder coated architectural bronze is standard. Other finishes are available upon request.
- **CERTIFICATION**
UL listed for wet locations.



ENTRANCE/WALKWAY LIGHT

Ordering Matrix

| Model | Wattage | Lamp | Voltage | Finish | Options |
|-------------|---------|------|---------|--------|-----------|
| CWPE | 70 | MH | 120 | BZ | PC |
| | 100 | HPS | 277 | BK | VS |
| | 150 | | 480 | WH | TP |
| | 175 | | MULTI | CC | GLR QZ |
| CWPE | 42 | CP | | | EM |

MH: Metal Halide
HPS: High Pressure Sodium
CP: Compact Fluorescent

BZ: Bronze Finish
BK: Black Finish
WH: White Finish
CC: Custom Color

PC: Photocell
VS: Vandal Shield
TP: Tamperproof hardware
GLR: Single Fuse
QZ: Quartz Restrike
EM: 90 Min. Remote Battery Back-Up
 (FOR FLUORESCENTS ONLY)

Example: If you wanted to specify a 150 watt, metal halide CWPE fixture with tamperproof hardware and black finish, the model number would read as follows:

CWPE – 150– MH – 120 – BK – TP

