



# EWB

JOB NAME:

FIXTURE TYPE:

## ***EXTERIOR WALL BRACKET***

### **FEATURES**

- High impact polycarbonate lens is designed for optimum light distribution.
- Optional wire guard is available upon request.
- Textured anodized aluminum reflector designed in conjunction with diffuser for maximum efficiency.
- ½" threaded apertures for surface conduit and/or optional photocell are provided for convenience during installation.
- All units are fully gasketed.
- For wall mounting directly over standard 4" outlet box or with surface conduit.
- Optional tamperproof hardware is available.

### **SPECIFICATIONS**

- **HOUSING**  
Rugged die cast aluminum housing.
- **ELECTRICAL**  
For metal halide lamping, ballast is high power factor, constant wattage auto aluminum housing for optimum heat dissipation. For high pressure sodium, ballast is normal power factor reactor type for 120V. High power factor, multi-tap, and most fixed voltages available.
- **SHIELDING**  
High impact polycarbonate lens standard.
- **FINISH**  
Baked on premium architectural bronze for maximum durability.
- **CERTIFICATION**  
All units bear UL and Made in U.S.A. label and are UL Listed for wet location.

# Exterior Wall Bracket

## Ordering Matrix

Model	Wattage	Lamp	Voltage	Finish	Options
EWB	70	MH	120	BZ	PC
		HPS	277	BK	WG
			480	WH	TP
			MULTI	CC	GLR QZ
EWB-F	42	CP			EM

**MH:** Metal Halide  
**HPS:** High Pressure Sodium  
**CP:** Compact Fluorescent

**BZ:** Bronze Finish  
**BK:** Black Finish  
**WH:** White Finish  
**CC:** Custom Color

**PC:** Photocell  
**WG:** Wire Guard  
**TP:** Tamperproof Hardware  
**GLR:** Single Fuse  
**QZ:** Quartz Restrike  
**EM:** 90 Min Emergency Battery Back-Up

**Example:** If you wanted to specify a 42-watt, compact fluorescent EWB fixture with tamperproof hardware and a remote battery back up and black finish, the model number would read as follows:

**EWB-F – 42 – CP – BK – TP – EM**

