



# GL

JOB NAME

FIXTURE TYPE

## **GL LUMINAIRE**

### **FEATURES**

- Available in
  - 150W-175W Metal Halide
  - 4 light 42W Compact Fluorescent
  - 85W Induction
- Ideal for parking areas, entrances, walkways, underpasses, loading docks, and on building exteriors.
- Anodized aluminum reflector offers high reflectivity and ease of maintenance.
- The Induction system is an electrode-less technology that offers an unprecedented 100,000 hour lamp life and is virtually maintenance free.
- This fixture works well in extreme conditions. The induction lamp operates in very cold temperatures and delivers up to 10 times the lumen output of the more traditional lighting in these environments.

### **SPECIFICATIONS**

- **HOUSING**  
Heavy duty die-cast aluminum housing. Bronze finish is standard.
- **ELECTRICAL**  
High Power Factor, constant wattage autotransformer available in fixed voltage or multi-tap.
- **REFLECTOR**  
Two piece aluminum reflector upper section removes to create uplight
- **CERTIFICATION**  
All units bear UL and Made in U.S.A. label. UL listed for wet location, covered ceiling mount only. 5 Year warranty on induction fixture.

# GL Luminaire

## Ordering Matrix

Model	Lamps	Wattage	Type	Voltage	Options
GL	1	150	MH	120	PC TP GLR QZ HS
		175		MULTI	
	2	CF			
	4				
1	85	IND			

**MH:** Metal Halide  
**CF:** Compact Fluorescent  
**IND:** Induction

**PC:** Photocell  
**TP:** Tamperproof hardware  
**GLR:** Single Fuse  
**QZ:** Quartz Restrike  
**HS:** 180° Cutoff Shield

**Example:** If you wanted to specify a 150HPS, GL fixture the model number would read as follows:

**GL- 150HPS**

