



LB

JOB NAME

FIXTURE TYPE

LOW BAY

FEATURES

- Available in Metal Halide 175W, 250W, and 400W and in High Pressure Sodium in 150W, 250W, and 400W.
- Ideal choice for low to medium mounting heights.
- Pendant mounting (for 3/4" conduit) is standard. Optional quick connect hook with 24" cord and NEMA twist lock plug for chain hanging.
- Injection molded acrylic refractor designed to maximize efficiency and distribution while controlling glare. Optional polycarbonate drop prismatic lens.
- Full gasketing around reflector and refractor reduce dirt contamination, extending lamp life and performance.
- Fixture includes clear mogul lamp.

SPECIFICATIONS

- **HOUSING**
Die cast aluminum with thermal chimney separating ballast core and coil from capacitor and igniter.
- **ELECTRICAL**
High Power Factor, constant wattage autotransformer available in 120, 208, 240, 277, 347, or 480V. Optional multi tap(120, 208, 240 or 277V) or tri tap (120, 240, 347V).
- **REFLECTOR**
Hydroformed aluminum reflector utilizes an IES type V distribution designed for maximum efficiency.
- **FINISH**
Entire fixture (housing and reflector) supplied with durable white acrylic base powder coat finish.
- **CERTIFICATION**
All units bear UL label, and Made in U.S.A. Suitable for 40°C ambient operations.



Low Bay

Ordering Matrix

Model	Wattage	Lamp	Voltage	Finish	Options
LB	70	MH	120	BZ	PC
	100	HPS	277	BK	TP
	150		480	WH	GLR
	175		MULTI	CC	QZ
					EM
LB-F	42	CP			

MH: Metal Halide
HPS: High Pressure Sodium
CP: Compact Fluorescent

BZ: Bronze Finish
BK: Black Finish
WH: White Finish
CC: Custom Color

PC: Photocell
TP: Tamperproof hardware
GLR: Single Fuse
QZ: Quartz Restrike
EM: 90 Min. Remote Battery Back-Up

Example: If you wanted to specify a 150 watt high pressure sodium LB fixture, the model number would read as follows:

LB – 150HPS

