

# WPB



JOB NAME:

FIXTURE TYPE:

## ***ENTRANCE/WALKWAY LIGHT***

### **FEATURES**

- Ideal for parking areas, entrances, walkways, underpasses, loading docks, recreation areas, and tunnels.
- Heavy-duty die-cast aluminum back housing.
- Color matched UV stabilized polycarbonate front housing with ribbed lens area.
- Front Housing is hinged for easy relamping
- One piece designed anodized aluminum reflector for optimum light efficiency.
- Silicon rubber seal prevents leakage.
- Lamping in compact fluorescent in 2-18 watt, 2-26 watt, 2-32 watt and 2-42 watt and 35W, 50W and 70W HPS available.

### **SPECIFICATIONS**

- **HOUSING**  
Heavy-duty die cast aluminum back housing.
- **ELECTRICAL**  
Compact fluorescent standard with universal voltage electronic ballast. HPS standard with 120 volt normal power factor magnetic core and coil ballast.
- **FINISH**  
Powder coated architectural bronze is standard. Other finishes are available upon request.
- **CERTIFICATION**  
UL listed for wet locations.



## Cut-Off Cast Aluminum Wall Bracket

### Ordering Matrix

Model	Wattage	Lamp	Voltage	Finish	Options
<b>WPB</b>	2/18	CF	UNV	BZ	PC
	2/26			BK	TP
	2/32			WH	GLR
	2/42			CC	QZ
<b>WPB</b>	70	HPS	<b>120</b>		

**HPS:** High Pressure Sodium  
**CF:** Compact Fluorescent

**BZ:** Bronze Finish  
**BK:** Black Finish  
**WH:** White Finish  
**CC:** Custom Color

**PC:** Photocell  
**TP:** Tamperproof hardware  
**GLR:** Single Fuse  
**QZ:** Quartz Restrike

**Example:** If you wanted to specify a 2-26 watt, compact fluorescent WPB fixture with tamperproof hardware and black finish, the model number would read as follows:

**WPB – 2/26– CF – UNV – BK – TP**