



WPE

JOB NAME:

FIXTURE TYPE:

WIDE THROW BEVELED WALL PACK

FEATURES

- Die cast aluminum housing with integral hinging feature for ease of maintenance.
- Prismatic glass lens optically designed for optimum light distribution.
- Optional polycarbonate shield or wire guard for vandalproof protection is available.
- Textured anodized aluminum reflector designed in conjunction with diffuser for maximum efficiency.
- Threaded apertures for conduit and optional photocell provided for the flexibility during installation.
- Fully gasketed weather resistant construction.
- Two sizes available. Lamping up to 400 watts.

SPECIFICATIONS

- **HOUSING**
Rugged die cast aluminum housing.
- **ELECTRICAL**
For metal halide lamping ballast is high power factor, constant wattage auto transformer. Electrical components are mounted to cast aluminum housing for optimum heat dissipation. For high-pressure sodium, ballast is normal power factor reactor type for 120V. High power factor, multi-tap, and most fixed voltages available.
- **SHIELDING**
Borosilicate glass is standard.
- **FINISH**
Baked on premium architectural bronze for maximum durability is standard.
- **CERTIFICATION**
All units bear UL and Made in U.S.A. labels. UL listed for wet and damp locations.



Cast Aluminum Exterior Wall Bracket

Ordering Matrix

Model	Wattage	Lamp	Voltage	Finish	Options
WPE	70	MH	120	BZ	PC
	100	HPS	277	CC	VS
	150		480		TP
	175	MULTI			GLR
	250				QZ
	400				WG

MH: Metal Halide
HPS: High Pressure Sodium

BZ: Bronze Finish
CC: Custom Color

PC: Photocell
VS: Vandal Shield
TP: Tamperproof hardware
GLR: Single Fuse
QZ: Quartz Restrike
WG: Wire Guard

Example: If you wanted to specify a 150W MH, WPE fixture with tamperproof hardware, the model number would read as follows:

WPE – 150 – MH – TP

