

WPF



JOB NAME:

FIXTURE TYPE:

ENTRANCE/WALKWAY LIGHT

FEATURES

- Ideal for parking areas, entrances, walkways, underpasses, loading docks, recreation areas, and tunnels.
- Heavy-duty die-cast aluminum back housing.
- One piece polycarbonate lens
- Aluminum reflector
- One piece designed anodized aluminum reflector for optimum light efficiency.
- Lamping options available in high pressure sodium, metal halide, and compact fluorescent.

SPECIFICATIONS

- **HOUSING**
Heavy-duty die cast aluminum back housing.
- **ELECTRICAL**
Compact fluorescent standard with universal voltage electronic ballast. HPS standard with 120 volt normal power factor magnetic core and coil ballast.
- **FINISH**
Powder coated architectural bronze is standard. Other finishes are available upon request.
- **CERTIFICATION**
UL listed for wet locations.



Cut-Off Cast Aluminum Wall Bracket

Ordering Matrix

Model	Wattage	Lamp	Voltage	Finish	Options
WPF	35	HPS	120	BZ	PC
	50		277	BK	TP
	70		UNV	WH	GLR
	100		CC	QZ	
	150				
	50	MH			
	70				
	100				
	26	CF			
	32				
	42				

HPS: High Pressure Sodium
MH: Metal Halide
CF: Compact Fluorescent

BZ: Bronze Finish
BK: Black Finish
WH: White Finish
CC: Custom Color

PC: Photocell
TP: Tamperproof hardware
GLR: Single Fuse
QZ: Quartz Restrike

