

WWB

JOB NAME:

FIXTURE TYPE:



EXTERIOR WALL BRACKET

FEATURES

- Die cast aluminum housing with integral hinging feature for ease of maintenance.
- Borosilicate prismatic glass optically designed for optimum light distribution.
- Optional polycarbonate shield for vandalproof protection over the glass refractor.
- Textured anodized aluminum reflector designed in conjunction with diffuser for maximum efficiency.
- Threaded apertures for conduit and optional photocell.
- Fully gasketed weather resistant construction.
- For wall mounting directly over standard 4" outlet box or with surface conduit.
- Optional stainless steel wire guard.
- Optional tamperproof hardware.

SPECIFICATIONS

- **HOUSING**
Rugged die cast aluminum housing.
- **ELECTRICAL**
Metal Halide High Reactance, High Power Factor, 120V/277V, dual tap. High Pressure Sodium Normal Power, reactor type for 120V only. High Power Factor and other voltages optional.
- **SHIELDING**
Borosilicate glass is standard. Polycarbonate is available as an option up to 150 watt.
- **FINISH**
Baked on premium architectural bronze for maximum durability.
- **CERTIFICATION**
All units bear UL label and Made in U.S.A.



Exterior Wall Bracket

Ordering Matrix

Model	Wattage	Lamp	Voltage	Finish	Options
WWB	70	MH	120	BZ	PC
	100	HPS	277	BK	TP
	150		480	WH	GLR
	175		MULTI	CC	QZ
WWBF	42	CP			EM

MH: Metal Halide
HPS: High Pressure Sodium
CP: Compact Fluorescent

BZ: Bronze Finish
BK: Black Finish
WH: White Finish
CC: Custom Color

PC: Photocell
TP: Tamperproof hardware
GLR: Single Fuse
QZ: Quartz Restrike
EM: 90 Min. Remote Battery Back-Up

Example: If you wanted to specify a 42-watt, compact fluorescent WWB fixture with tamperproof hardware and a remote back up and black finish, the model number would read as follows:

WWBF – 42 – CP – BK – TP – EM

