

SW66

JOB NAME:

FIXTURE TYPE:

WALL MOUNTED SURFACE LUMINAIRE

FEATURES

- Available in 2', 3', and 4' lengths, 1 and 2 lamp configurations, T8 and T12.
- Wall mount brackets included for 1' spacing. (Two are required for 2', 3', and 4'. Three are required for 6' and 8'.)
- 6x6 narrow design is architecturally preferred for installation in corridors, lobbies, and office areas.
- For individual or continuous row mounting.
- Direct downlight is standard. Indirect and direct/indirect applications are available.
- Ends seams are fitted to provide the appearance of continuous row mounting.
- Knockouts on channel ends allow for through wiring or end feed.
- For full complement of accessories to ease installation, refer to **Options** section.
- Custom colors available to match any décor.
- Available with energy efficient reflectors in specular silver (95% reflectance) or specular aluminum (85% reflectance).


SPECIFICATIONS

- **HOUSING**
Die formed and welded heavy gauge cold rolled steel.
- **ELECTRICAL**
Energy saving and electronic class P, HPF ballasts comply with Federal Energy Efficiency standards.
- **SHIELDING**
Acrylic prismatic is standard. Optional white cross baffle and semi-specular cross baffle. Refer to **Options** for additional shielding.
- **FINISH**
All metal parts post painted with premium grade white enamel with a minimum 89% reflectance applied over iron phosphate pretreatment for maximum adhesion and rust resistance.
- **CERTIFICATION**
All units bear UL and Made in U.S.A. label.




ORDERING INFORMATION



WALL DIRECT




WALL DIRECT-INDIRECT




WALL INDIRECT




DIRECT



DIRECT / INDIRECT



DIRECT / INDIRECT



INDIRECT

(Shown with optional wall mount brackets)

CATALOG NUMBER	LAMPS	LENGTH	CATALOG NUMBER T8	LAMPS	LENGTH
SW66-120	1-F20	24-1/2"	SW66-117	1-FO17T8	24-1/2"
SW66220	2-F20	24-1/2"	SW66-217	2-FO17T8	24-1/2"
SW66-130	1-F30	36-1/2"	SW66-125	1-FO25T8	36-1/2"
SW66-230	2-F30	36-1/2"	SW66-225	2-FO25T8	36-1/2"
SW66-140	1-F40	48-1/2"	SW66-132	1-FO32T8	48-1/2"
SW66-240	2-F40	48-1/2"	SW66-232	2-FO32T8	48-1/2"

For critical application verify all dimensions with factory.
For additional Lamp/Ballast options, consult factory.

Options:

- Electronic Ballast – suffix SSB-T8 or SSB-T12
- White Cross Baffle – suffix WCB
- Parabolic (semi-specular) Cross Baffle – suffix PBL
- Custom Color – suffix CC (color)
- Indirect – suffix IND
- Direct/Indirect – suffix D/I
- Specular Silver Reflector – suffix SS95
- Specular Aluminum Reflector – suffix SA85