

MP-M-4

JOB NAME

FIXTURE TYPE



FOUR HEADED REMOTE EMERGENCY LIGHT

FEATURES

- Compact unit that accommodates 4 remote adjustable fixtures.
- Ideal for public, commercial, and industrial facilities with varied unit load requirements.
- Metal incandescent heads are standard. Optional plastic or weatherproof heads.
- Remote battery powered. Available in 6 volt, 12 volt and 24 volt
- Battery units have low voltage disconnects that prevents possible over-discharge of battery. Automatic brownout protection is standard.
- Test switch and indicator pilot light are standard.
- Optional voltmeter.
- Overall dimension are 8" x 8 "x 8" with standard heads.
- Mounts to 4" octagon box

SPECIFICATIONS

HOUSING

18 gauge die formed steel can accommodate up to 4 remote head units.

BATTERY

6, 12 or 24 volt, maintenance free, sealed lead calcium for 120V/277V system.

FINISH

Powder coat in Architectural white.

LAMPS

Glass sealed PAR36 5.4 watt high intensity tungsten lamps are standard.

CERTIFICATION

All units bear UL label and Made in the U.S.A. labels. Meets or exceed NEC, OSHA, NFPA, and most state and local codes. New York City and Chicago approved units available.

